



■ Waveguide Port Correspondence Table

Chinese Standard	EIA Standard	Frequency range(GHz)	Wide edge(mm)	Narrow edge(mm)	Commonly Used CPR Flange	Commonly Used UG Flange
BJ-22	WR-430	3.22~4.90	109	55	CPR-430	UG-1248
BJ-26	WR-340	3.95~5.85	86	43	CPR-340	UG-1187
BJ-32	WR-284	4.90~7.05	72	34	CPR-284	UG-1153
BJ-40	WR-229	6.57~9.99	58	29	CPR-229	UG-387/U
BJ-48	WR-187	7.90~11.70	48	22	CPR-187	UG-447/U
BJ-58	WR-159	9.84~14.50	40	20	CPR-159	UG-385/U
BJ-70	WR-137	11.90~18.00	35	16	CPR-137	UG-348/U
BJ-84	WR-112	14.50~22.00	29	13	CPR-112	UG-1387/U
BJ-100	WR-90	17.60~26.70	23	10	CPR-90	UG-389/U
BJ-120	WR-75	21.70~33.00	19	10	CPR-75	UG-187/U
BJ-140	WR-62	26.40~40.00	16	8	CPR-62	UG-383/U
BJ-180	WR-51	33.00~50.00	13	6	CPR-51	UG-153/U
BJ-220	WR-42	40.00~60.00	11	4	CPR-42	UG-195/U
BJ-260	WR-34	49.00~75.00	9	4	CPR-34	UG-217/U
BJ-320	WR-28	60.00~90.00	7	4	CPR-28	UG-381/U
BJ-400	WR-22	75.00~110.0	6	3	CPR-22	UG-380/U